

HP LaserJet P2014 Printer series



Rely on the high-quality HP LaserJet P2014 Printer to produce professional-looking, black-and-white documents at fast print speeds, with easy compatibility, and all at an affordable price.



HP LaserJet P2014 Printer

The perfect choice for small workteams and privileged professionals in any sized business who need a compact, black-and-white printer that offers good value, professional quality, powerful performance and reliability.

Powerful performance at an affordable price.

Enjoy the dependable, high-quality output you expect from HP, combined with the performance you need – all at an affordable price. The compact HP LaserJet P2014 Printer features a 264 MHz processor and 32 MB memory for robust printing. Print any type of office document of almost any length with a 250-sheet input tray, and expand the paper input capacity with the optional 250-sheet tray. The 50-sheet multipurpose tray supports a wide range of media.

Print professional-looking documents quickly.

Make a great first impression with true 1200 dpi at full engine speed. Print professional-quality documents with crisp text and sharp images, quickly and reliably. Increase productivity with print speeds of up to 23 ppm. No-wait Instant-on Technology delivers a first page out in less than 8.5 seconds – even from Powersave mode. The reliable all-in-one HP LaserJet print cartridge is designed to meet your usage needs, optimise print quality and provide excellent value.

This compact LaserJet printer fits your office environment.

The highly reliable HP LaserJet P2014 Printer delivers a premium Windows Vista experience and supports numerous other operating systems, so you can change or update your operating system and still keep your printer. Connect easily via USB or parallel port to a standard PC or server. Add network capabilities with an optional HP Jetdirect External Print Server. The space-saving design lets you make the most of your work area.

Technical specifications

Print technology	Laser			
Print speed	A4 black: Up to 23 ppm First page out black: < 8.5 sec (instant-on with no warm-up time)			
Processor	264 MHz, Pensilica			
Memory	32 MB, Not expandable			
Print resolution	Up to 1200 x 1200 dpi			
Print quality	HP FastRes 1200, HP ProRes 1200			
Printer languages	HP PCL 5e, host-based			
Economical printing	Economode (saves toner), return to PowerSave mode after print job due to instant-on technology (saves electricity), N-up printing (saves paper)			
Typefaces/fonts	Intellifont 26			
Duty cycle	Up to 10000 pages per month			
Print margins	top: 4 mm, left: 4 mm, right: 4 mm, bottom: 4 mm			
Media handling	Input	Capacity	Weight	Size
	Tray 1	sheets: 50	60 to 163 g/m ² (straight through paper path for special media)	A4, A5, A6, B5, B6, envelopes (C5, DL), 76 x 127 to 216 x 356 mm
	Tray 2	sheets: 250	60 to 120 g/m ²	A4, A5, B5, 147 x 211 to 216 x 356 mm
	Tray 3 (optional)	sheets: 250	60 to 120 g/m ²	A4, A5, B5, 147 x 211 to 216 x 356 mm
	Output: Sheets: Up to 150. Envelopes: Up to 10. Transparencies: Up to 75; 150-sheet output bin			
	Duplex printing: Manual (driver support provided)			
Media types	Paper (bond, light, heavy, plain, recycled, rough), envelopes, labels, cardstock, transparencies, heavy media			
Interface and connectivity	Hi-Speed USB (compatible with USB 2.0 specifications), IEEE 1284-B compliant parallel port, optional: HP Jetdirect en1700 IPv4/IPv6 Print Server, HP Jetdirect en3700 Fast Ethernet Print Server, HP Jetdirect ew2400 802.11g Wireless Print Server			
Operating systems compatibility	Windows® 98 SE; Windows® 2000; Windows® Me (print driver only); Windows® XP Home; Windows® XP Professional; Windows® Server 2003; Mac OS X v10.2.8; Mac OS X v10.3.9; Mac OS X v10.4.3 Optional: Windows® 98 SE, 2000, Me, NT 4.0, XP Home, XP Professional, XP Professional x64, Server 2003, Windows Vista™ x32, Windows Vista™ x64; Mac OS X v10.2.8, 10.3.9, 10.4.3 and higher; UNIX; Linux; HP OpenVMS; OS/2, Solaris® 2.5x, 2.6, 7, 8 (SPARC® systems only), latest drivers and software available at http://www.hp.com/			
Network operating systems compatibility	optional: Via optional HP Jetdirect external print server: Windows® 98 SE, 2000, Me, XP Home, XP Professional, XP Professional x64, Server 2003, Windows Vista™ x32; Windows Vista™ x64, Novell® NetWare 3.2, 4.2, 5.x, 6; Mac OS v10.2.8, 10.3.9, 10.4.3; Linux RED HAT Linux 6.x and higher; SUSE Linux 6.x and higher; UNIX HP-UX 10.20, 11.x; Solaris® 2.5x, 2.6, 7, 8 (SPARC® systems only); MPE-iX			
Minimum system requirements	Windows® 98: Pentium®, 166 MHz, 64 MB RAM; Windows® 2000, XP Home, XP Professional: 333 MHz processor, 64 MB RAM; Windows® Server 2003: 550 MHz processor, 128 MB RAM; 200 MB available hard disk space (all systems), Mac OS X v10.2.8, 10.3, 10.4, 10.5 and higher; 128 MB RAM minimum (256 MB recommended), 150 MB available hard disk space			
Software	HP printer software on CD-ROM: installer/uninstaller, drivers (HP PCL 5e, Host-based), control panel simulator, help, documentation			
Control panel	6 lights (Jam, Toner low, Paper out, Attention, Ready, Go), 2 buttons (Go, Cancel)			
Power	Requirements: Input voltage: 110 to 127 VAC (+/- 10%), 60 Hz (+/- 2 Hz); 220 to 240 VAC (+/- 10%), 50 Hz (+/- 2 Hz). Consumption: 410 watts maximum (active, printing), 7 watts maximum (ready, sleep), 0.1 watts maximum (off)			
Dimensions (w x d x h)	Out of package: 350 x 362 x 256 mm Packaged: 430 x 330 x 480 mm			
Weight	Out of package: 10.3 kg Packaged: 13.2 kg			
Operating environment	Operating temperature: 0 to 45 ° C. Recommended operating temperature: 15 to 32.5° C. Operating humidity: 10 to 80% RH. Recommended operating humidity: 30 to 70% RH. Storage temperature: -20 to 60 ° C. Storage humidity: 10 to 80% RH. Noise level per ISO 9296: Sound power: LwAd 6.4 b(A) (active, printing), inaudible (ready). Sound pressure: LpAm 50 dB(A) (active, printing), inaudible (ready)			
Product certifications	Safety certifications: IEC 60950-1 (International), EN 60950-1 (EU), IEC 60825-1+A1+A2, UL/cUL Listed (US/Canada), GS License (Europe), EN 60825-1+A1+A2 Class 1, 21 CFR Ch. 1/SubCh. J (Class 1 Laser/LED Device) GB4943-2001, Low Voltage Directive 73/23/EEC with CE Marking (Europe). Other safety approvals as required by individual countries			
Warranty	One-year, return to HP authorised service centre			

Ordering information

CB450A	HP LaserJet P2014 Printer, HP LaserJet print cartridge (Q7553A), Getting Started Guide, CD (containing device software and User's Guide), power cord
Accessories	
Q5931A	HP 250-sheet Accessory Tray
Supplies	
Q7553A	HP LaserJet Q7553A Black Print Cartridge with Smart Printing Technology 3,000 standard pages in accordance with ISO/IEC 19752
Q7553X	HP LaserJet Q7553X Black Print Cartridge with Smart Printing Technology 7,000 standard pages in accordance with ISO/IEC 19752
Connectivity	
J7942G	HP Jetdirect en3700 External Print Server (USB, 10/100TX)
J7951G	HP Jetdirect ew2400 802.11g Wireless and Fast Ethernet External Print Server
J7988G	HP Jetdirect en1700 External Print Server
C6518A	HP USB Cable, 2m
Service & support	
H2634A/E	HP Care Pack, Return to HP, 3 years
H5465A/E	HP Care Pack, Next Business Day Exchange, 3 years
H5473A/E	HP Care Pack, Next Business Day On-Site, 3 years
H2639PA/PE	HP Care Pack, Post Warranty Next Business Day On-Site, 1 year
U8047PA/PE	HP Care Pack, Post Warranty, Return to HP, 1 year
H3110A/E	HP Care Pack, Installation and Network Configuration

For a complete list of supplies, accessories and services, please refer to <http://www.hp.com>

<http://www.hp.com/uk>



© Copyright Hewlett-Packard Development Company, L.P. 2007. The information contained herein is subject to change without notice. The only warranties for HP Products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

Published in EMEA 05/07 4AA1-2596EEE

